

Introducing
3M™ DBI-SALA®
Nano-Lok™
Extended Length
Self-Retracting
Lifelines - 20 ft.

Going to great lengths to help improve fall protection.

We're advancing the versatility of 3M™ DBI-SALA® Nano-Lok™ SRLs. Available in 9 ft., 11 ft., 15 ft. and now 20 ft. lengths, the family of Nano-Lok SRLs combines fall protection with ease-of-use and versatility for even more applications.

- Speed sensing brake activation system provides protection at low heights.
- Tension is always kept on the lifeline, which helps reduce dragging, snapping and trip falls.
- Durable nitrile energy absorber is a smaller design and last four times longer.


Explore the full range of Nano-Lok SRLs at **3M.com/FallProtection**





Designed to go the distance.

Expanding the length to create even more 3M™ DBI-SALA® Nano-Lok™ SRL models to meet your requirements.





3M™ DBI-SALA® Nano-Lok™ Self-Retracting Lifelines

Lifeline Material	Length	Connector	Anchor Mount	Part #
Kevlar [®]	11	Swiveling Steel Snap Hook	Steel Carabiner	3101684
Dyneema®	20	Steel Snap Hook	Steel Carabiner	3103865
Dyneema®	20	Swiveling Steel Snap Hook	Steel Carabiner	3103866
Dyneema®	20	Aluminum Carabiner	Aluminum Carabiner	3103872
Dyneema®	20	Swiveling Stainless Steel Snap Hook	Stainless Steel Carabiner	3103873
Galvanized Cable	15	Swiveling Steel Snap Hook	Steel Carabiner	3501694
Stainless Steel Cable	15	Swiveling Stainless Steel Snap Hook	Stainless Steel Carabiner	3501695

The above SKUs are For Overhead Use Only.

Explore the full range of Nano-Lok SRLs at

3M.com/FallProtection



3M Fall Protection 3833 SALA Way Red Wing, MN 55066 USA Phone 800.328.6146

Email 3mfallprotection@mmm.com Web 3M.com/FallProtection

Swiveling Anchorage Loop Limits lifeline twisting

Limits lifeline twisting for smooth operation.

Impact-Resistant Housing

Tough thermoplastic housing designed to withstand demanding worksites.

Speed-Sensing Brake System

As low as 6 ft. of required fall clearance.

Dyneema® Fiber and Polyester Web Lifeline

Synthetic lifeline reduces overall weight and the retractable design provides freedom of movement.

High-Capacity External Energy Absorber

Durable nitrile energy absorber is a smaller design and last four times longer.

> Maintains safe fall arrest forces for users (and tools) up to 420 lbs. (190 kg)

Impact Indicator

Provides a visual alert that the SRL has been involved in a fall.

20 ft Nano-Lok SRL



