

Fyxate™ ANSI CSA



DIELECTRIC



FOAM
PADDING



RUBBER
NOSEPIECE



RUBBER
TIPS



INCLUDES
STRAP

Dielectric

Rubber temple tips and nosepiece

Single wraparound lens

Foam padding available on select options

Quick release strap available on foam padded options only

Part No.	Lens and Temples	
SB10210S ●●		Clear
SB10210ST ●●	AF	Clear H2X
SB10220S ●●		Gray
SB10220ST ●●	AF	Gray H2X
SB10280S ●●		I/O Mirror
Part No.	Foam Padded	
SB10210STMFP ●●	AF	Clear H2MAX
SB10220STMFP ●●	AF	Gray H2MAX



vimeo.com/pyramex/h2max



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

Safety eyewear meets ANSI Z87.1+ standards [●] and Canadian CSA Z94.3 [●] – SEI third-party certification. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted and provides 99% protection from harmful UV rays.

Fyxate™

General Specifications

Weight: 23.2 gm and 46.35 gm (with foam)
 Bridge: 12.8 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.5 mm
 Lens size vertical: 42.72 mm
 Lens thickness: 1.95 mm
 Overall length (lens - tip): 160.8 mm
 Overall width (hinge - hinge): 129 mm
 Closest point between temple tips: 73 mm

Materials

Lens: polycarbonate
 Nosepiece: thermoplastic rubber (TPR)
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Foam gasket: nylon and ethylene-vinyl acetate (EVA)
 Strap: polyester

Part No.	Lens Marking	Temple Marking
SB10210S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10210ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10220S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10220ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10280S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10210STMFP	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10220STMFP	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% max visible light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967