



# Cobra Cart™

## Mobile Fall Arrest Systems

### Meets OSHA Requirements

1910.29(b) and 1926.502(b)

With multiple workers on a job site requiring personal fall arrest systems, the Cobra Cart is the solution. Cobra Cart offers workers OSHA compliant anchor points when doing leading-edge work.

With anchor points for 2 people for fall restraint and up to 3 for fall arrest, Cobra Cart provides up to a 45-degree work zone in either direction of the anchor point.

For fall arrest, the Cobra Cart engagement claw quickly penetrates the substrate to secure the cart. Utilize the optional rescue winch for recovery. Open area allows for mounting of a generator, compressor, or toolbox. Fork pockets and lift points simplify transport and lifting.

Built "roofer" tough with powder coated surfaces for durability and corrosion resistance. The flat-free tires allow easy repositioning.

### Cobra Cart Standard



### Cobra Cart Deluxe



## Why Choose Garlock Safety Systems™?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- Full Passive Fall Prevention Portfolio
- In-House Engineering
- Custom Engineered Products Available



# Features



**Integrated Handle/Brake**



**Engagement Claw**



**Cobra Cart Anchor Points**  
yellow = fall restraint  
green = fall arrest

# Specifications

## Cobra Cart Standard

## Cobra Cart Deluxe

Part Number	301463	301528
Fall Arrest Rating	3 people*	
Fall Restraint Rating	2 people	
Tool Box	<b>Optional</b> Poly 7.5 ft <sup>3</sup> "	<b>Standard</b> Steel 8.5 ft <sup>3</sup> "
Parking Brakes	Optional	Standard
Material Rack	Not Available	Standard
Rescue Winch	Optional	
Fall Alert	Optional	
Deck Space - Front	22" x 40"	
Deck Space - Rear	26" x 40"	None
Length (with handle)	102"	
Width	59"	
Height	36"	52"
Weight	1100 lbs	
Tires	Flat Free 18 x 8.50	

\* on 4000PSI concrete slab rated for 1 person only

# Options



### **Parking Brakes** P/N: 301088

Option for Cobra Cart standard only.  
(Included with Cobra Cart deluxe)



### **Self Retracting Lifeline Tray** P/N: 460-010-003

Tray is compatible with the standard and deluxe versions. It can hold up to three 50' SRLs and keeps them elevated off the surface to protect them from debris to extend the life of this investment.



### **Rescue Winch** P/N: 301117

Aid in retrieval of fallen workers.



### **Fall Alert** P/N: 301124

Warn other workers a fall has occurred.



P : 877.791.4446  
E : [safetyorders@garlockequip.com](mailto:safetyorders@garlockequip.com)  
GARLOCKSAFETY.COM

Address:  
2601 Niagara Ln N.  
Plymouth, MN 55447