


Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Lanyards with energy absorber




ABSORBICA-I International version

Single lanyard with integrated compact energy absorber designed for protection on a horizontal lifeline (rope or cable) or on an elevated platform. It is available in 80 or 150 cm versions (without connectors). Equipped with two captive carabiners, it is certified to U.S. and European standards.



ABSORBICA-I single lanyards are designed particularly for protection on a horizontal lifeline or on an elevated platform.



In case of a fall, the tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 50 and 130 kg. The progressive tearing of the webbing reduces the deceleration on lightweight users.



The energy absorber is very compact to avoid hindering the user's movements, or interfering with handling. A durable fabric pouch helps protect the energy absorber from abrasion and potential contaminants.

Short Description Single lanyard with integrated energy absorber and captive carabiners

- Selling Points**
- Designed for protection on a horizontal lifeline (rope or cable) or on an elevated platform
 - Absorbs energy in case of a fall:
 - tearing of the energy absorber webbing limits the impact force on the user
 - works with users who weigh between 50 and 130 kg
 - progressive tearing reduces the deceleration on lightweight users
 - Minimal bulk: compact energy absorber facilitates handling
 - Abrasion resistance:
 - durable zippered fabric pouch protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
 - lanyard and pouch reduce the risk of cuts and potential severing over edges
 - Comes with two captive steel carabiners, with TRIACT-LOCK autolocking system.
 - Available in two lengths: 100 and 170 cm

-
- Specification**
- Material(s): polyester, nylon, steel
 - Certification(s): ANSI Z359.13 12 feet, ANSI Z359.12, CE EN 355, CE EN 354, CE EN 362
-

Specifications by reference

Reference(s)	L64IU 80	L64IU 150
		
	100 cm	170 cm
	195 cm	305 cm
	395 cm	575 cm
Weight	870 g	930 g
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	3
Case quantity	0	0
EAN	3342540103313	3342540103979

Related product(s) VOLT