


Universe	Professional
Туре	Verticality
Category	Mobile fall arresters
Subcategory	Absorbers for mobile fall arresters




## ASAP'SORBER AXESS

The ASAP'SORBER AXESS energy absorber may only be used with the ASAP or ASAP LOCK mobile fall arrester. It allows user to work at a distance from the rope, in order to protect it during certain work phases. Equipped with tear-webbing inside a pouch that opens on each end, the absorber is protected from abrasion, while allowing for regular inspection. In can be used in two-person rescue situations for a maximum load of 250 kg.



The ASAP'SORBER AXESS allows the rope to be kept at a distance to protect it during certain work phases.



The ASAP'SORBER AXESS can be used for loads up to 250 kg in two-person rescue situations.

## **Short Description** Energy absorber for ASAP or ASAP LOCK for a maximum load of 250 kg **Selling Points** • May only be used with an ASAP or ASAP LOCK mobile fall arrester • Allows the user to keep the rope at a distance in order to: - free up the work area - protect the rope from sharp tools and harmful contact points • Absorbs energy in case of a fall: - tearing of the energy absorber webbing limits the impact force on the user - designed for users who weigh between 50 and 130 kg Can be used for loads of up to 250 kg in two-person rescue - durable fabric pouch with opening system at each end, protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber • Ends equipped with STRING to hold the connector in position and protect the webbing from abrasion Specification • Material(s): nylon, polyester • Certification(s): CE EN 355, ANSI Z359.13 6 feet

## Specifications by reference

Reference(s)	L071CB00
Length	40 cm
Weight	205 g
Made in	RO
Guarantee	3 years
Inner Pack Count	1
Quantity Per Box	20
EAN	3342540831360

ASAP® LOCK ASAP® Related product(s)

ASAP®
OK
Bm'D
OXAN
CAPTIV
AXIS 11 mm with sewn termination
ASAP'AXIS 11 mm
BAY 11 mm with sewn termination

RAY 11 mm with sewn termination