



The LifePoint Standard tie-off anchor is the perfect solution for fall prevention when circumstances require non-penetrating versatility.

Non-Penetrating Versatility:

The LifePoint is a mobile safety harness tie-off device that provides fall prevention for two people: Fall arrest for one and fall restraint for one at the same time, or fall restraint for two. LifePoint standard is a complete fall arrest system and works without penetrating the roof. When the LifePoint is set in place on the roof deck it provides the fall resistance needed to protect two people. This is a non-penetrating tie off anchor that works on flat surfaces such as single ply membrane, BUR, concrete, TPO, and EPDM roofs.

Easy:

LifePoint can be set up quickly. The base is set in place and the individual counterweights are added. Using the patented transport cart, LifePoint can be moved to a new location quickly and safely by a single person.

Built to Last:

Whether you transport LifePoint job to job, or use it as a permanent tie-off on your rooftop, LifePoint will provide years of fall prevention.

2 Anchorage Capability:

LifePoint Deluxe provides fall protection anchor points for the following:

- (1) person fall restraint and (1) person fall arrest or
- (2) person fall restraint.





Why Choose Garlock Safety Systems™?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available



Specifications

Base

Dimensions	28.5"x 24"x 13" (LxWxH)
Weight Fully Assembled	960 lbs
Counterweights	57 lbs each (14 required)
Approved Surface Use	Poured Concrete, EDPM (adhered & loose laid), TPO (adhered & loose laid), BUR (swept)
Finish	Powder-coated for corrosion resistance

Due to continuous improvement, specifications are subject to change without notice.

Transport Cart (optional)

Dimensions	97"x58"x24" (LxWxH)
Weight Fully Assembled	112 lbs

Options



Optional transport cart.



Optional Lifepoint protective cover.