UNITED STATES


COMPLIANCE
WITHOUT COMPROMISE



capital SAFETY

PROTECTA®

TRUSTED, QUALITY FALL PROTECTION | FULL LINE CATALOG | 2015


COMPLIANCE PEOPLE LOVE US.
BOSSES BREATHE EASIER.
THE GUYS KNOW WE HAVE THEIR BACK.



COMPLIANCE PEOPLE AROUND THE WORLD AGREE, WHEN IT COMES TO FALL PROTECTION AND RESCUE, PROTECTA® IS A GLOBAL PARTNER.

It seems like there are fewer things you can count on every year. That's what makes Protecta stand out in fall protection and rescue. Under some of the harshest conditions around the globe, for more than 79 years, Protecta has proven its reliability job after job.

Protecta gear provides a combination of practical affordability and simple compliance. Our extensive line of safety equipment ranges from basic harnesses and lanyards to complex, industry-specific anchorage connectors with no compromise on quality. Protecta has many of the same features as higher priced equipment, such as ergonomic design, impact indicators, serial numbers, steel hardware, accessories and options for specialized needs and budgets. Protecta gear meets or exceeds the world's most stringent standards and codes—ANSI, OSHA, CSA and CE, as well as local and state codes.

TABLE OF CONTENTS

Introduction, Pgs. 4-5

Harnesses, Pgs. 6-11

Lanyards, Pgs. 12-19

Self Retracting Lifelines, Pgs. 20-23

Vertical & Horizontal Systems, Pgs. 24-27

Anchorage Connectors, Pgs. 28-31

Fall Protection Kits, Pgs. 32-35

Confined Space & Rescue, Pgs. 36-37

Protecta® is part of Capital Safety—the only company with global reach solely dedicated to fall protection and rescue—but we don't just manufacture equipment. Our leaders participate in compliance regulatory organizations. Our product specialists are on-site soliciting direct input from workers. Once you've chosen Protecta, we're there with training and long-term product support.



PROTECTA®: A SURE THING IN



LIFETIME WARRANTY

Protecta products are warranted for their entire lifetime to be free from defects in materials and workmanship, under normal use and conditions. Our warranty extends from the product's original date of purchase, in new or unused condition, from any authorized Protecta brand distributor and applies exclusively to the product's end user. For detailed warranty information, see *www.capitalsafety.com*.



TRAINING AND CONSULTING

We offer training in every aspect of fall protection and rescue, either on-site or at one of our three North American training centers. We also offer custom and industry-specific courses, as well as printed and video training tools in various languages. You can order them at *www.capitalsafety.com* or call us toll-free anytime.

A WORLD OF UNCERTAINTY.

THE ABC's OF FALL PROTECTION

The ABC's are an easy way to remember the components of fall protection. "A" stands for Anchorage, "B" is Body support and "C" is the Connection between them. Don't forget "D"—Descent and rescue equipment that must be on-site at each job.

Anchorages are a secure point of attachment. Anchorage connectors vary by industry, job, type of installation and structure. They must be able to hold fast under more than a ton of force generated in a fall.

Body Support harnesses distribute fall forces over the upper thighs, pelvis, chest and shoulders. They provide a connection point on the worker for the personal fall arrest system.

Connectors, such as shock absorbing lanyards or self retracting lifelines, connect the worker's harness to the anchorage.

Descent and Rescue devices are used to retrieve an injured worker or lower him to the ground.



MODELS WITH COMFORT PADDING
Shoulders, back and legs are cushioned for increased comfort and additional security in a fall.

DORSAL D-RING
High-quality alloy steel for strength and durability. Adjustable for worker convenience.

LANYARD KEEPERS
Provides place to "park" lanyard when not in use to prevent accidental entanglements.

SPRING LOADED TORSO BUCKLES
Provide fast and easy adjustment on the job.

BUILT-IN IMPACT INDICATOR
Allows for easy inspection, added safety.

BODY BELT AND HIP PAD
Added lumbar support, positioning capabilities and tool carrying support/options.

LIGHTWEIGHT HARDWARE
Reduces weight and fatigue. Increases comfort and productivity.



Model Shown 1191209

MULTIPLE CONNECTION POINTS
Add versatility, allowing harness to be used for many different jobsite applications.

TONGUE BUCKLE LEGS
Simple, fast and easy adjustment. Ideal when more than one worker uses a harness.

Other leg strap buckles available:



Quick Connect Buckle

Pass-Thru Buckle

INCREASED CAPACITY
Complete protection for workers up to 420 lbs. (190 kg).

IMPROVED FIT
Greater sizing flexibility, comfort and overall performance.

THEY COVER YOUR CREW AND YOUR REAR END AT THE SAME TIME.



Model Shown 1191260

PRO™ SERIES The all new, fully functional Protecta® PRO line gives you the right harness, the right fit and the right value. With a design that incorporates an improved fit, updated colors and lightweight hardware and padding, they provide greater comfort and added safety, which means reduced worker fatigue and increased productivity. Plus, each harness now features built-in lanyard keepers and an increase in worker capacity — up to 420 lbs. (190 kg). PRO harnesses meet OSHA and ANSI standards, including the stringent ANSI Z359.1.

PRO™ HARNESS ACCESSORIES

AK048A
EQUIPMENT BAG
Compact harness/lanyard bag, 13" x 12" (33 cm x 30 cm).



AK066A
EQUIPMENT BAG
Large bag for harness and lanyard or 50 ft. (15 m) lifeline, 9-1/2" x 10" x 15-1/2" (24 cm x 25 cm x 40 cm).



PRO BODY BELT
Tongue buckle belt with hip pad and side D-rings.

1091013 Small

1091014 Medium/Large

1091015 X-Large



1385000
PRO D-RING EXTENSION
Dorsal D-ring extender with D-ring at one end, snap hook at other x 18" (45 cm).



PRO™ CONSTRUCTION HARNESSES



PRO CONSTRUCTION STYLE POSITIONING HARNESS

Back D-rings, hip pad and belt with side D-rings, shoulder pads, tongue buckle legs.

1191208 Small

1191209 Medium/Large

1191210 X-Large



PRO CONSTRUCTION STYLE POSITIONING HARNESS

Back D-rings, hip pad and belt with side D-rings, shoulde pads, pass-thru leg straps.

1191226 Small

1191227 Medium/Large

1191228 X-Large



PRO CONSTRUCTION STYLE POSITIONING HARNESS WITH COMFORT PADDING

Back D-rings, hip pad and belt with side D-rings, back and leg padding, quick connect legs.

1191269 Small

1191270 Medium/Large

1191271 X-Large



PRO CONSTRUCTION STYLE POSITIONING HARNESS WITH COMFORT PADDING

Back D-rings, hip pad and belt with side D-rings, tongue buckle leg straps, moisture wicking comfort padding.

1191432 Small

1191433 Medium/Large

1191434 X-Large

PRO™
VEST-STYLE HARNESSES



PRO VEST-STYLE HARNESS

Back D-ring, tongue buckle legs.

1191236 Small

1191237 Medium/Large

1191238 X-Large



PRO VEST-STYLE HARNESS

Back D-ring, pass-thru buckle legs.

1191200 Small

1191201 Medium/Large

1191202 X-Large



PRO VEST-STYLE HARNESS WITH COMFORT PADDING

Back D-ring, shoulder, back and leg padding, quick connect buckle legs.

1191252 Small

1191253 Medium/Large

1191254 X-Large



PRO VEST-STYLE HARNESS WITH COMFORT PADDING

Back D-ring, tongue buckle leg straps, moisture wicking comfort padding.

1191429 Small

1191430 Medium/Large

1191431 X-Large



PRO VEST-STYLE HARNESS

Back and side D-rings, tongue buckle legs.

1191245 Small

1191246 Medium/Large

1191247 X-Large



PRO VEST-STYLE HARNESS

Back and side D-rings, pass-thru buckle legs.

1191204 Small

1191205 Medium/Large

1191206 X-Large



PRO VEST-STYLE HARNESS WITH COMFORT PADDING

Back and side D-rings, shoulder, back and leg padding, quick connect buckle legs.

1191259 Small

1191260 Medium/Large

1191261 X-Large



PRO VEST-STYLE CLIMBING HARNESS WITH COMFORT PADDING

Back and front D-rings, tongue buckle leg straps, moisture wicking comfort padding.

1191437 Medium/Large

1191438 X-Large

1191439 2X-Large



PRO™ HARNESSES FOR HOT WORK



For Hot Work Use

PRO VEST-STYLE HARNESS FOR HOT WORK USE

Back D-ring, Kevlar® fiber webbing, pass-thru buckle legs.

1191369 Small

1191379 Medium/Large

1191380 X-Large



For Hot Work Use

PRO VEST-STYLE HARNESS FOR HOT WORK USE

Back and side D-rings, Kevlar® fiber webbing, pass-thru buckle legs.

1191370 Small

1191381 Medium/Large

1191382 X-Large



For Hot Work Use

PRO VEST-STYLE HARNESS FOR HOT WORK USE

Back D-ring, Kevlar® fiber webbing, tongue buckle legs.

1191371 Small

1191383 Medium/Large

1191384 X-Large



For Hot Work Use

PRO VEST-STYLE HARNESS FOR HOT WORK USE

Back and side D-rings, Kevlar® fiber webbing, tongue buckle legs.

1191372 Small

1191385 Medium/Large

1191386 X-Large

PRO™ CLIMBING HARNESSES



PRO CLIMBING HARNESS

Back and front D-rings, tongue buckle legs.

1191272 Small

1191273 Medium/Large

1191274 X-Large



PRO CLIMBING HARNESS

Back and front D-rings, pass-thru buckle legs.

1191233 Small

1191234 Medium/Large

1191235 X-Large

PRO RETRIEVAL HARNESSES



PRO RETRIEVAL HARNESS

Back and shoulder D-rings, tongue buckle legs.

1191240 Small

1191241 Medium/Large

1191242 X-Large



PRO RETRIEVAL HARNESS


Back and shoulder D-rings, pass-thru buckle legs.

1191215 Small

1191216 Medium/Large

1191217 X-Large

PRO HARNESS SIZING CHART



REDUCED IMPACT FORCES
Built-in energy absorber limits the average fall arresting forces to 900 lbs. (4kN) for added safety.

HIGH STRENGTH AND CAPACITY
5,000 lb. (22kN) breaking strength for durability and 310 lb. (140 kg) capacity for worker flexibility.

3,600 lb. GATED HOOKS
Every PRO™ lanyard features 3,600 lb. gated hooks, for added safety and security.

TOUGH WEBBING
Polyester construction is strong enough to endure rough use and the elements.

IMPACT INDICATOR
Allows for easy inspection for added safety.

VARIOUS STYLES AND LENGTHS
A variety of styles and lengths are available to choose from—if you don't see it, please call.

DURABLE HARDWARE
Alloy steel construction with zinc plating for strength, durability and corrosion resistance.



Model Shown 1340101

HOOK OPTIONS

All Protecta® lanyards feature 3,600 lb. (16kN) gated hooks for added safety.



STANDARD HOOK WITH 3/4" (19 mm) GATE OPENING
3,600 lb. (16kN) gate strength.



FLAT STEEL REBAR HOOK WITH 2-1/4" (57 mm) GATE OPENING
3,600 lb. (16kN) gate strength.



TIE-BACK CARABINER WITH A 3/4" (19 mm) GATE OPENING
5,000 lb. (22kN) gate strength.

FOR YOU IT'S COMPLIANCE. TO A CREW IT'S CONFIDENCE.

Protecta® PRO™ lanyards provide high quality compliance at an economical price. And trust among workers. They feature 3,600 lb. gated hooks, durable lanyard material construction and plated alloy steel hardware for strength and corrosion resistance. All PRO™ shock absorbing lanyards limit the average fall arresting forces to 900 lbs. (4kN) and meet OSHA and ANSI standards, including the stringent ANSI Z359.1.

PRO PACK

PRO Shock Absorbing lanyards feature durable 1" (25 mm) polyester webbing, 1/2" (13 mm) nylon rope or 1/4" (6 mm) vinyl covered cable with 3,600 lb. (16kN) gated hooks and an energy absorbing design that limits the average fall arresting forces to 900 lbs. (4kN) for added safety.



PRO HOT WORKS

PRO Hot Works shock absorbing lanyards feature flame resistant Kevlar® fiber webbing and shock pack. Includes 3,600 lb. (16kN) gated hooks and an energy absorbing design that limits the average fall arresting forces to 900 lbs. (4kN) for added safety.



PRO TIE-BACK

PRO Tie-back shock absorbing lanyards feature specialized webbing and hardware that withstands the rigors of tie-back use. Includes 3,600 lb. (16kN) gated hooks and an energy absorbing design that limits the average fall arresting forces to 900 lbs. (4kN) for added safety.



PRO-STOP™

PRO-Stop lanyards feature polyester tubular web, as opposed to a traditional shock pack, 3,600 lb. (16kN) gated hooks and an energy absorbing design that limits the average fall arresting forces to 900 lbs. (4kN) for added safety.



PRO ELASTIC

PRO Elastic shock absorbing lanyards combine the pack style energy absorber with stretch capabilities. It expands to 6 ft. (1.8 m) and contracts to 4-1/2 ft. (1.4 m) in reaction to the worker's movements. The 3,600 lb. (16kN) gated hooks and an energy absorber design limit the average fall arresting forces to 1800 lbs. (8kN) for added safety.



PRO STRETCH

PRO Stretch lanyards feature a polyester tubular web that expands to 6 ft. (1.8 m) and contracts to 4-1/2 ft. (1.4 m) in reaction to the worker's movements, 3,600 lb. (16kN) gated hooks and an energy absorbing design that limits the average fall arresting forces to 1,800 lbs. (8kN) for added safety.



PRO POSITIONING

All PRO Positioning lanyards feature 3,600 lb. (16kN) gated hooks and are used to maintain a working position. These devices do not incorporate shock absorbers and can only be used without a fall arrest system if the fall possibility is 2 ft. (0.6 m) or less.



PRO™ PACK SHOCK ABSORBING LANYARDS



1341001
PRO SHOCK ABSORBING LANYARD

Single-leg with snap hooks at each end x 6 ft. (1.8 m)

1341004 4 ft. (1.2 m) length

1341002 3 ft. (0.9 m) length



1341050
PRO ADJUSTABLE SHOCK ABSORBING LANYARD

Single-leg, adjustable in length, snap hooks at each end x 6 ft. (1.8 m)



1340125
PRO SHOCK ABSORBING LANYARD

Single-leg with snap hook and flat steel rebar hook x 6 ft. (1.8 m)



1342001
PRO 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with snap hooks at each end x 6 ft. (1.8 m)



1342250
PRO ADJUSTABLE 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg, adjustable length, snap hooks at each end x 6 ft. (1.8 m)

1342275 Double-leg, adjustable length, rebar hooks at each end x 6 ft. (1.8 m)



1340180
PRO 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8 m)

1340181 5 ft. (1.5 m) length



1340401
PRO CABLE SHOCK ABSORBING LANYARD

Single-leg with self locking snap hooks x 6 ft. (1.8 m)



1340451
PRO CABLE 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with self locking snap hooks x 6 ft. (1.8 m)



1340701
PRO ROPE SHOCK ABSORBING LANYARD

Single-leg with snap hooks at each end x 6 ft. (1.8 m)



1340751
PRO 100% TIE-OFF ROPE SHOCK ABSORBING LANYARD

Double-leg with snap hooks at each end x 6 ft. (1.8 m)

PRO™ LANYARDS FOR HOT WORK USE



1340128
PRO SHOCK ABSORBING LANYARD FOR HOT WORK USE

Single-leg with Kevlar® fiber webbing and shock pack, snap hook at one end, steel rebar hook at other end. x 6 ft. (1.8 m)



1340185
PRO 100% TIE-OFF SHOCK ABSORBING LANYARD FOR HOT WORK USE

Double-leg with Kevlar® fiber webbing and shock pack, flat steel rebar hooks at each end x 6 ft. (1.8 m)



1340129
PRO SHOCK ABSORBING LANYARD FOR HOT WORK USE


Single-leg with Kevlar® fiber webbing and shock pack, snap hooks at each end x 6 ft. (1.8 m)



1340187
PRO 100% TIE-OFF SHOCK ABSORBING LANYARD FOR HOT WORK USE

Double-leg with Kevlar® fiber webbing and shock pack, snap hooks at each end x 6 ft. (1.8 m)

PRO™ TIE-BACK SHOCK ABSORBING LANYARDS



1340200
PRO TIE-BACK SHOCK ABSORBING LANYARD

Single-leg with floating D-ring for tie-back and snap hooks x 6 ft. (1.8 m)



1342200
PRO TIE-BACK 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with floating D-rings for tie-back and snap hooks x 6 ft. (1.8 m)



1340040
PRO TIE-BACK SHOCK ABSORBING LANYARD

Single-leg with 5,000 lb. (22 kN) carabiner for tie-back and snap hook x 6 ft. (1.8 m)



1340060
PRO TIE-BACK 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with 5,000 lb. (22 kN) carabiners at leg ends for tie-back and snap hook x 6 ft. (1.8 m)

PRO-STOP™ SHOCK ABSORBING LANYARDS



1340220
PRO-STOP SHOCK ABSORBING LANYARD

Single-leg with self locking snap hooks at each end x 6 ft. (1.8 m)



1340230
PRO-STOP SHOCK ABSORBING LANYARD

Single-leg with self locking snap hook and flat steel rebar hook x 6 ft. (1.8 m)



1340240
PRO-STOP 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with self locking snap hooks at each end x 6 ft. (1.8 m)



1340250
PRO-STOP 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with self locking snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8 m)

PRO™ ELASTIC SHOCK ABSORBING LANYARDS



1341101
PRO ELASTIC SHOCK ABSORBING LANYARD

Single-leg with snap hooks at each end x 6 ft. (1.8 m)

1341102 4 ft. (1.2 m) length



1342101
PRO ELASTIC 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with snap hooks at each end x 6 ft. (1.8 m)




1342125
PRO ELASTIC 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8 m)

Every PRO™ lanyard features 3,600 lb. (16kN) gated hooks for added safety and security on the jobsite. The hooks also incorporate high strength, corrosion resistant materials for added durability and longevity.



PRO™ STRETCH SHOCK ABSORBING LANYARDS



1340101
PRO STRETCH SHOCK ABSORBING LANYARD

Single-leg with snap hooks at each end x 6 ft. (1.8 m)



1340121
PRO STRETCH SHOCK ABSORBING LANYARD

Single-leg with snap hook and flat steel rebar hook x 6 ft. (1.8 m)



1340141
PRO STRETCH 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with snap hooks at each end x 6 ft. (1.8 m)



1340161
PRO STRETCH 100% TIE-OFF SHOCK ABSORBING LANYARD

Double-leg with snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8 m)



ACCESSORIES



1340260
PRO SHOCK ABSORBER

Shock absorber (ONLY) with D-ring at one end, snap hook at other x 18-1/2" (47 cm)

Add in-line to a non-shock absorbing lanyard for fall arrest applications



1385000
PRO D-RING EXTENSION

Dorsal D-ring extender with D-ring at one end, snap hook at other x 18" (45 cm)


PROTECTA

PRO™ POSITIONING LANYARDS



1385101
PRO WEB POSITIONING LANYARD

Single-leg with snap hooks at each end x 6 ft. (1.8 m)

1385102 3 ft. (0.9 m) length



1385301
PRO ADJUSTABLE WEB POSITIONING LANYARD

Single-leg, adjustable length with snap hooks at each end x 6 ft. (1.8 m)



1385501
PRO ROPE POSITIONING LANYARD

Single-leg with snap hooks at each end x 6 ft. (1.8 m)



1351001
PRO WEB REBAR ASSEMBLY

Swiveling web rebar assembly with snap hooks and flat steel rebar hook at center x 24" (61 cm)




1351050
PRO WEB REBAR ASSEMBLY

Web rebar assembly with snap hooks and flat steel rebar hook at center x 22" (56 cm)



1350150
PRO CHAIN REBAR ASSEMBLY

Swiveling chain rebar assembly with snap hooks and flat steel rebar hook at center x 24" (61 cm)




1350200
PRO CHAIN REBAR ASSEMBLY

Chain rebar assembly with snap hooks and flat steel rebar hook at center x 22" (56 cm)


Rebel

STILL USING A LANYARD? UPGRADE TO THE REBEL™ 6 FT. SRL.

Example of Fall Clearance Requirements of the Rebel 6 ft. SRL vs. Similar Lanyard Length.



*Always refer to instructions for fall clearance

310 lb. (141 kg) CAPACITY
Meets a wide range of user weights.

TRIPLE ACTION CARABINER
For easy connection to anchorage point or harness.



IMPACT RESISTANT
Thermoplastic housing – lightweight, compact and durable.

HEAT-SHRUNK
Clear PVC coating over EVA foam label on shock pack for improved durability.

HIGH STRENGTH
Thin webbing for added durability and longevity.

Model Shown 3100403

COMPLIANT
Fully OSHA and ANSI compliant.

SPECIFICATIONS

Single		100% Tie-off	
3100403 Steel Snap Hook with Carabiner		**3100412** Steel Snap Hook with Carabiner	
3100404 Steel Swiveling Snap Hook with Carabiner		**3100413** Steel Swiveling Snap Hook with Carabiner	
3100405 Steel Rebar Hook with Carabiner		**3100414** Steel Rebar Hook with Carabiner	

ECONOMICAL. DEPENDABLE. SAFE.

With a Rebel™ Self Retracting Lifeline (SRL), you get an economical fall protection solution that won't compromise the safety or performance of your crew. Rebel continues to set performance standards beyond compliance, while providing a substantial value compared to competitive models.

IMPROVED SHOCK PACK DESIGN (6' - 20' UNITS)

RUGGED, LIGHTWEIGHT HOUSING

RECESSED LABLES TO INCREASE PRODUCT LIFE

IMPACT INDICATOR

SWIVELING ANCHORAGE

3,600 LB. GATE CAPACITY

420 LB. MODELS AVAILABLE (33' UNITS AND ABOVE)



3100432
REBEL 20 Ft. (6.1 m) SRL

20 ft. (6.1 m) of 1" (2.5 cm) polyester web with steel swiveling snap hook, swiveling anchorage and carabiner.

3590019
REBEL 15 Ft. (4.5 m) SRL

15 ft. (4.5 m) of 3/16" (5 mm) galvanized steel wire rope with steel swiveling snap hook, swiveling anchorage and carabiner.



3100425
REBEL 11 Ft. (3.3 m) SRL

11 ft. (3.3 m) of 1" (2.5 cm) polyester web with steel snap hook, swiveling anchorage and carabiner.





3100426
REBEL 11 Ft. (3.3 m) SRL

11 ft. (3.3 m) of 1" (2.5 cm) polyester web with steel swiveling snap hook, swiveling anchorage and carabiner.



3100427
REBEL 11 Ft. (3.3 m) SRL

11 ft. (3.3 m) of 1" (2.5 cm) polyester web with steel rebar hook, swiveling anchorage and carabiner.

DOZENS OF WAYS TO STAY COMPLIANT WITHOUT COMPROMISE.

Web/Cable Length													6' (1.8 m)	11' (3.3 m)	15' (4.5 m)	20' (6 m)	33' (10 m)	50' (15 m)	66' (20 m)	85' (26 m)	100' (30 m)
Lifeline Material	Thermoplastic Housing	Aluminum Housing	Stackable	Impact Indicator	Swiveling Anchorage	Self Locking Snap Hook	Rebar Hook	Swiveling Hook	Leading Edge	100% Tie-Off	310 lb. (140 kg) Weight Capacity	420 lb. (190 kg) Weight Capacity									
Galv Cable	•				•	•		•			•		3590015	3590016	3590019						
	•				•	•					•				3590018						
	•		•	•	•	•		•				•				3590517	3590500	3590550	3590590	3590630	3590670
		•	•	•	•	•		•				•				3590514	3590510	3590560	3590600	3590640	3590680
	•		•	•	•	•		•	•		•					3590540					
	•				•	•	•				•				3590020						
SS Cable	•		•	•	•	•		•				•				3590504	3590501	3590551	3590591	3590631	3590671
		•	•	•	•	•		•				•				3590509	3590511	3590561	3590601	3590641	3590681
Web	•				•	•					•		3100403	3100425		3100431					
	•				•	•		•			•		3100404	3100426		3100432					
	•				•	•	•				•		3100405	3100427		3100433					
	•				•	•				•	•		3100412								
	•				•	•		•		•	•		3100413								
	•				•	•	•			•	•		3100414								
											Weight		Varies	Varies	Varies	Varies	13.5 lb. (6.1 kg)	17.3 lb. (7.8 kg)	22 lb. (10 kg)	28.6 lb. (13 kg)	29.5 lb. (13.4 kg)
											Approximate depth		2" (5 cm)	3" (8 cm)	3" (8 cm)	4.6" (12 cm)	4.6" (12 cm)	4.6" (12 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)
											Approximate width		3.5" (8.9 cm)	6" (15 cm)	6" (15 cm)	9.8" (14 cm)	9.8" (24.9 cm)	11" (28 cm)	12.8" (33 cm)	12.8" (33 cm)	12.8" (33 cm)
											Approximate height*		19" (48 cm)	19" (48 cm)	29" (74 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	23.8" (61 cm)	25.7" (65 cm)	25.7" (65 cm)	25.7" (65 cm)

*Anchor point to anchor point

Standards: Meets OSHA 1926.502, OSHA 1910.66, ANSI Z359.1, ANSI 2359.12, ANSI A10.32, CSA Z259.2.2 Type II



See Pages 34-35 Confined Space & Rescue Section for Rebel™ 3-Way SRL's with Built-In Emergency Retrieval



HINT: NEVER CHOOSE AN INFERIOR LIFELINE FOR A BIG GUY WITH A HAMMER.





Model 1200101

Protecta® offers reliable vertical and horizontal lifeline systems that not only ensure a worker's safety, but complement his ability to work. PRO™, Cobra™ and Cabloc™ are established performers in many industries and meet applicable standards, including OSHA.



HORIZONTAL LIFELINE SYSTEM

1200101

PRO-LINE™ SYNTHETIC HORIZONTAL LIFELINE SYSTEM

The PRO-Line synthetic horizontal lifeline systems are lightweight, easy to install and extremely portable. Just disassemble and take to the next job.

- Complete kit includes two tie-off adaptors for simple anchorage to structure
- Built-in shock absorber reduces anchorage loadings to preserve the structure
- Fall arrest rated for two users provides jobsite flexibility
- 60 ft. (18 m) web lifeline is compact, portable and versatile

1200105 PRO-Line Synthetic Horizontal Lifeline System x 60 ft. (18 m) with carrying bag (no tie-off adaptors)



LADDER SAFETY SLEEVE

AC351A

CABLOC™ LADDER SAFETY SLEEVE

The Cabloc device is for use on fixed ladder safety systems. It offers complete hands-free operation, and arrests a fall within 2 ft. (0.6 m). It travels on a 3/8" (9.5mm) 7x19 solid core cable affixed to a ladder or pole, utilizing an upper and lower bracket.

AC350A Cabloc Ladder Safety Sleeve for use on 5/16" (8 mm) 7x19 solid core cable

ROPE GRABS – AUTO AND MANUAL

AC202D
COBRA™ ROPE GRAB (Auto / Manual)



- Mobile design automatically follows user for hands-free operation
- Manual option allows user to fix unit in place for positioning or restraint
- Detachable design can be attached or removed anywhere along lifeline
- For use on 5/8" (16 mm) nylon rope lifeline

5000003
ROPE GRAB (Auto)



- Mobile design automatically follows user for hands-free operation
- Detachable design can be attached or removed anywhere along lifeline
- For use on 5/8" (16 mm) polyester/ polypropylene rope lifeline
- Lightweight and compact design

1340005
PRO ROPE ADJUSTER/LANYARD (Manual)



- Manual design allows user to fix unit in place for positioning or restraint
- Attached 2 ft. (0.6 m) shock absorbing lanyard
- For use on 5/8" (16 mm) polyester/ polypropylene rope lifeline

LIFELINES

AC215A
LIFELINE - NYLON

50 ft. (15 m) nylon rope lifeline with attached snap hook.

AC210A1	25 ft. (7.6m), 5/8" (16 mm) nylon, carabiner at one end, taped at other
AC210A2	25 ft. (7.6m), 5/8" (16 mm) nylon, snap hooks at both ends
AC215A1	50 ft. (15m), 5/8" (16 mm) nylon, carabiner at one end, taped at other
AC215A2	50 ft. (15m), 5/8" (16 mm) nylon, snap hooks at both ends
AC225A1	75 ft. (22m), 5/8" (16 mm) nylon, carabiner at one end, taped at other
AC230A1	100 ft. (30m), 5/8" (16 mm) nylon, carabiner at one end, taped at other

1299997
LIFELINE - POLYESTER/POLYPROPYLENE

50 ft. (15m) polyester/polypropylene blended rope lifeline with attached snap hook.

1299996	25 ft. (7.6 m), 5/8" (16 mm) blended polyester/polypropylene, snap hook at one end, taped at other
1299991	30 ft. (9 m), 5/8" (16 mm) blended polyester/polypropylene, snap hook at one end, taped at other
1299992	75 ft. (22 m), 5/8" (16 mm) blended polyester/polypropylene, snap hook at one end, taped at other
1299998	100 ft. (30 m), 5/8" (16 mm) blended polyester/polypropylene, snap hook at one end, taped at other





ANCHORS MADE FOR CONCRETE, WOOD, STEEL AND PEACE-OF-MIND.

Anchorage connectors are dependent on specific job requirements—the type of attachment, environment and connecting system. That's why we offer the most complete line, all rigorously tested to meet OSHA and ANSI standards and ensure strength. Our anchorages are a secure point of attachment capable of supporting a load of 5,000 lbs. (22kN) per worker. An anchorage connector attaches your personal fall arrest system to the main anchorage or support structure.

GENERAL (ALL-PURPOSE) ANCHORS

Portable anchors used in a variety of applications. Many are "choker" style designed to provide a safe and easy way to anchor a fall protection device to an overhead location beyond normal reach.



STEEL ANCHORS

Anchors for steel are often used during commercial construction and attached to steel columns and beams. Models can be permanently attached or temporarily clamped, offering a fixed or mobile anchorage connector.



CONCRETE ANCHORS

Concrete anchors are secured to concrete decks and columns. They provide the worker with safety and mobility when performing concrete construction work.



ROOF ANCHORS

Roof anchors are available in a variety of designs to meet the specific requirements of your roof type. They are designed to keep the worker safe, without causing damage to the structure.



GENERAL (ALL-PURPOSE) ANCHORAGE CONNECTORS

Our tie-off adaptors are our most versatile anchorage connector combining ease of use, light weight and 5,000 lb. (22kN) high strength.


AJ450A6


AJ47410

AJ450A6
WEB TIE-OFF ADAPTOR

Pass-through design makes attaching to anchorage quick and easy. 1-3/4" polyester strength member with 3" wide polyester wear pad x 6 ft. (1.8 m).

AJ450A	Web tie-off adaptor x 3 ft. (0.9 m)
AJ47410	Web tie-off adaptor x 6 ft. (1.8 m) with web loop and D-ring pass-thru
AJ47410A3	Web tie-off adaptor x 3 ft. (0.9 m) with web loop and D-ring pass-thru

AJ408AG
CABLE TIE-OFF ADAPTOR

Lightweight and extremely durable 1/4" (6.4 mm) coated galvanized cable stands up to harsh environments. 6 ft. (1.8 m) length with snap hook at one end, O-ring at the other.

AJ47406 Cable tie-off adaptor with two O-rings


AJ408AG

2190102
CABLE TIE-OFF ADAPTOR

1/4" galvanized 7x19, with carabiner at one end and two D-rings at other x 6 ft.


2190100

2190100	Cable tie-off adaptor with carabiner at one end and two D-rings at the other x 3 ft.
2190101	Cable tie-off adaptor with carabiner at one end and two D-rings at the other x 4 ft.

Carabiners are an extremely versatile choice to keep your system securely connected. Workers appreciate the reduced weight and easy operation they offer. 5,000 lb. (22kN) minimum breaking strength for added safety.



2000112
CARABINER

Steel carabiner with 3,600 lb. (16kN) self closing/ locking gate, 11/16" (17.5 mm) opening.

2000117	Carabiner, roll pin, 11/16" (1.75 cm) opening
2000114	Carabiner 2-3/16" (5.56 cm) opening

STEEL ANCHORAGE CONNECTORS

Extremely versatile anchors for steel are lightweight and compact, providing an easy to install and safe 5,000 lb. (22kN) tie-off point for your personal fall protection system.



AJ704A
BEAMDOG™ SLIDING BEAM ANCHOR

For use on top or below an I-beam with flanges 4" to 14-3/4" (10 cm - 37.4 cm) wide and up to 1-1/2" (3.8 cm) thick. Nylon rollers provide smooth, effortless operation along the beam.



AJ703A
RAILDOG™ SLIDING RAIL ANCHOR

Provides mobile anchor point on 2-3/4" to 3-1/4" (7 cm - 8.25 cm) wide rails. Incorporates stainless steel construction and special 5,000 lb. (22kN) gate rated carabiner.

AN111A
EYEBOLT ANCHOR - UNTHREADED


Unthreaded ring only (no bolt), forged steel construction with zinc plating, 1-1/2" ID anchor area.



AN112A
EYEBOLT ANCHOR - THREADED

Forged steel construction with zinc plating, 1/2" x 1-3/8" mounting bolt, 2-3/4" ID horizontal anchor area, 1-3/8" ID vertical anchor area.





AJ301A
HAND GRIP

2" (5 cm) capacity. One hand operation with plastic grips for comfort.

AJ302A	Hand Grip with 3" (7.6 cm) capacity
AJ303A	Hand Grip with 4" (10 cm) capacity

CONCRETE ANCHORAGE CONNECTORS

Our concrete anchors are lightweight and compact, providing an easy to install and safe 5,000 lb. (22kN) tie-off point for your personal fall protection system.



2190053
REUSABLE CONCRETE WEDGE ANCHOR

Portable, durable and safe concrete anchor for vertical wall or overhead ceiling applications. Easy to use for added safety and flexibility.

2190055
CONCRETE D-RING ANCHOR

Simple, versatile and safe concrete anchor for temporary or permanent applications. Extremely rugged design for extended life and jobsite flexibility.

2190060 Concrete D-ring anchor with 6 bolts



2190057
CONCRETE ANCHOR STRAP

Pack of 25 disposable anchor straps with D-ring x 3-1/2 ft. (1 m) is designed to provide a temporary anchorage on concrete forms. Loop slips over rebar, then concrete is poured over. When no longer needed, simply cut strap and discard.

2190058 Concrete Anchor Strap with D-Ring x 4 ft. (1.2 m) - Pack of 25

2190063 Concrete Anchor Strap without D-Ring x 3-1/2 ft. (1 m) - Pack of 25



AJ720A
CONCRETE ANCHOR PLATE

Mounts horizontally or vertically to concrete or steel and includes forged D-ring for tie-off point.



AN220A
CONTINUOUS CONCRETE INSERT ANCHOR

Provides mobile anchor in standard strut material. Stainless steel plates with steel carabiner. Accommodates 1-5/8" (4.1 cm) wide strut material.



ROOF ANCHORS

We offer a complete array of anchorage devices for sloped wood and flat commercial steel roofs to help you customize the perfect fall protection solution.

AJ730A
PORTABLE REUSABLE ROOF ANCHOR

For use on flat or sloped wood roofs. Installs with 20 ea. 16D nails. Simple hinge style design is extremely easy to transport, install, dismantle and store.

2103680
KNOCK DOWN DISPOSABLE ROOF ANCHOR KIT

Simply nail into sheathing and roof member. When job is complete, knock down or shingle over. Kit contains 12 anchors and nails.

2103678
PERMANENT RIDGE ROOF ANCHOR

Installs with nails at the roof ridge. Shingle over leaving only the D-ring exposed. Provides fall protection during initial construction as well as for future homeowner.



AJ730A 2103680 2103678

2190001
STANDING SEAM SWIVELING ROOF ANCHOR

Portable and reusable anchor fits seam spacing of 12" to 24" (30 cm-61 cm). Non-penetrating clamp design won't damage the roof. Universal self retracting lifeline (SRL) cradle fits most SRLs and swivels 360° for maximum mobility and protection. (Shown with Rebel™ SRL—must order separately).



2190011
METAL/WOOD SWIVELING ROOF ANCHOR

Portable and reusable anchor provides 360° of mobility and protection on sloped or flat wood and metal decking. Universal bracket accommodates most self retracting lifelines. (Shown with Rebel™ SRL—must order separately.)





IT'S THIS SIMPLE: IT'S ALL IN THE CAN.



COMPLIANCE IN A CAN™

A complete fall protection system in one handy container!

Often imitated, never matched. Protecta® pioneered the creation of a complete fall protection system available in a convenient container. The success of the original "can" spawned the creation of several variations with different anchorage devices. Each kit offers a complete set-up for convenient OSHA compliance and safety on the job.

WHAT'S ALL IN THE CAN

See chart on next page for available combinations



1191995
Pass-thru
buckle legs



AB17550
Tongue buckle
legs

5-POINT HARNESS FOR VERSATILITY

5-point universal size harnesses meet a wide variety of jobsite requirements.



1340250



1340220



1340240



1341001

PRO™ 6 FT. SHOCK ABSORBING LANYARDS



3590500



3100425

REBEL™ SELF RETRACTING LIFELINE

33 ft. (1 m) or 11 ft. (3.3 m) retractable lifeline provides added mobility, reduced fall clearance and limits fall arrest forces to OSHA and ANSI requirements.

ANCHORAGE DEVICES

All-purpose, steel, concrete and roof type anchor choices are available to suit your jobsite.



AJ408AG



AJ720A



AJ730A



AJ47410



1340005

PRO ROPE ADJUSTER WITH SHOCK ABSORBING LANYARD AND ROPE LIFELINE

Compact, lightweight manual adjuster with 2 ft. (0.6 m) shock absorbing lanyard (1340005) stays locked in place on the 50 ft. (15 m) 5/8" polyester/polypropylene lifeline (1204001).



1204001



COMPLIANCE IN A CAN™

KIT COMPONENTS

CIAC SKU	QTY	Harnesses		Connectors							Anchors				Lifeline
		1191995	AB17550	1340005	1341001	1340220	1340240	1340250	3100425	3590500	AJ730A	AJ720A	AJ408AG	AJ47410	1204001
2199803	1	●		●							●				●
2199811	25	●		●							●				●
2199812	1	●		●								●			●
2199807	1	●		●									●		●
2199815	1	●		●										●	●
2199816	25	●		●										●	●
2199814*	1		●	●							●				●
2199819	1	●							●					●	
2199829	1	●								●	●				

COMPLIANCE IN A CAN LIGHT

KIT COMPONENTS

CIAC SKU	QTY	Harnesses		Connectors					Anchors				Lifeline
		1191995	AB17550	1340005	1341001	1340220	1340240	1340250	AJ730A	AJ720A	AJ408AG	AJ47410	1204001
2199802	1	●			●								
2199805	12	●			●								
2199806	48	●			●								
2199809	1	●				●							
2199810	1	●				●						●	
2199818	1		●				●						
2199817	1		●					●					
2199808*	1	●			●								

*The 2199814 and 2199808 are in a bag, not a bucket.



LEG LOCKS
Built into head to ensure legs stay locked in place.

BUILT-IN ANCHOR POINTS
Four eyebolts offer secondary anchor points for a fall arrest system.

PULLEY
Routes winch/SRL lifeline over opening providing smooth operation.

ALUMINUM CONSTRUCTION
Extremely lightweight yet durable construction for ease of use and longevity.

MECHANICAL DEVICES
Can support winches or SRLs for complete flexibility.

ADJUSTABLE LOCKING LEGS
Fast and easy detent pin style adjustment allows for precise height setting.

TELESCOPING LEGS
Provide fast and easy adjustment.

FOOT PADS
Skid resistant treadplate soles on feet.

SAFETY CHAIN
Provides added support and strength for demanding confined space applications.

WHEN EVERY SECOND COUNTS, THERE IS NO SECOND BEST.

Lightweight, portable Protecta® aluminum tripods are ideal for confined space manhole entry and retrieval. They're easily transported from one location to another and can be set-up by one worker. Attach one or two mechanical devices and you're ready to go. Built to meet OSHA and ANSI standards including the stringent ANSI Z359.1.

CONFINED SPACE COMPONENTS



AK105A
CONFINED SPACE TRIPOD

- 8 ft. (2.4 m) height
- 5,000 lb. (22 kN) 1-man rated
- Fast and simple installation
- Anodized epoxy coated aluminum

AK020A1
PULLEY WITH CARABINER



- Routes winch/SRL lifeline
- Anodized aluminum construction
- Pivoting sheave pulley guide
- Includes carabiner


AK020A pulley without carabiner

3591000
REBEL™ 3-WAY SELF RETRACTING LIFELINE



- 50 ft. (15 m) galvanized cable
- 310 lb. (140 kg) man rated capacity
- Fast and simple installation
- Fall arrest device with built-in emergency retrieval winch
- Models available with mounting brackets (or separately)

	50'	50' With Bracket
SS	3591001	3591007
Galv	3591000	3591006



3590498 Rebel 3-Way SRL Brackets, 3590497 SRL side bracket and 8008005 tripod side bracket

AK205AG
CONFINED SPACE WINCH



- 50 ft. (15 m) galvanized cable
- 310 lb. (140 kg) man rated capacity
- Fast and simple installation
- 4:1 ratio at 20 fpm

AK205AT Winch with 50 ft. (15 m) fiber rope lifeline

	30'	50'	60'	75'	110'
SS	AK203AS	AK205AS	AK206AS	AK207AS	AK210AS
Galv	AK203AG	AK205AG	AK206AG	AK207AG	AK210AG

CONFINED SPACE SYSTEMS

8308005	AK105A tripod, 3591000 Rebel SRL 50 ft. (15 m) 3-Way with galvanized cable, 3590498 bracket set, AK020A1 pulley with carabiner, AK067A carrying bag
8308006	AK105A tripod, 3591001 Rebel SRL 50 ft. (15 m) 3-Way with stainless steel cable, 3590498 bracket set, AK020A1 pulley with carabiner, AK067A carrying bag
AA805AG	AK105A tripod, AK205AG winch, 3590550 Rebel 50 ft. (15 m) galvanized SRL, AK020A1 pulley, 1191201 harness
AA805AG1	AK105A tripod, AK205AG winch, 3590550 Rebel 50 ft. (15 m) galvanized SRL, AK020A1 pulley (no harness)
AA805AG2	AK105A tripod, AK205AG winch, 3590550 Rebel 50 ft. (15 m) galvanized SRL, AK067A tripod bag, 1191201 harness

PART NUMBER & PAGE INDEX

1091013..... 7
1091014..... 7
1091015..... 7
1191200..... 9
1191201..... 9, 37
1191202..... 9
1191204..... 9
1191205..... 9
1191206..... 9
1191208..... 8
1191209..... 6, 8
1191210..... 8
1191215..... 11
1191216..... 11
1191217..... 11
1191226..... 8
1191227..... 8
1191228..... 8
1191233..... 11
1191234..... 11
1191235..... 11
1191236..... 9
1191237..... 9
1191238..... 9
1191240..... 11
1191241..... 11
1191242..... 11
1191245..... 9
1191246..... 9
1191247..... 9
1191252..... 9
1191253..... 9
1191254..... 9
1191259..... 9
1191260..... 7, 9
1191261..... 9
1191269..... 8
1191270..... 8
1191271..... 8
1191272..... 11
1191273..... 11
1191274..... 11
1191369..... 10
1191370..... 10
1191371..... 10
1191372..... 10
1191379..... 10
1191380..... 10
1191381..... 10
1191382..... 10
1191383..... 10
1191384..... 10
1191385..... 10
1191386..... 10
1191429..... 9
1191430..... 9
1191431..... 9
1191432..... 8
1191433..... 8
1191434..... 8
1191437..... 9
1191438..... 9
1191439..... 9
1191995..... 34, 35
1200101..... 25, 26
1200105..... 26
1204001..... 34, 35
1299991..... 27
1299992..... 27
1299996..... 27
1299997..... 27
1299998..... 27
1340005....27, 34, 35
1340040..... 15
1340060..... 15
1340101..... 12, 17
1340121..... 17
1340125..... 14
1340128..... 15
1340129..... 15
1340141..... 17
1340161..... 17
1340180..... 14
1340185..... 15
1340187..... 15
1340200..... 15
1340220... 16, 34, 35
1340230..... 16
1340240....16, 34, 35
1340250....16, 34, 35
1340260..... 17
1340401..... 14
1340451..... 14
1340701..... 14
1340751..... 14
1341001....14, 34, 35
1341002..... 14
1341004..... 14
1341050..... 14
1341101..... 16
1341102..... 16
1342001..... 14
1342101..... 16
1342125..... 16
1342200..... 15
1342250..... 14
1342275..... 14
1350200..... 19
1351001..... 19
1351050..... 19
1385000..... 7, 17
1385101..... 19
1385102..... 19
1385301..... 19
1385501..... 19
2000112..... 30
2000114..... 30
2000117..... 30
2103678..... 31
2103680..... 31
2190001..... 31
2190011..... 31
2190053..... 31
2190055..... 31
2190057..... 31
2190058..... 31
2190060..... 31
2190063..... 31
2190100..... 30
2190101..... 30
2190102..... 30
2199802..... 35
2199803..... 35
2199805..... 35
2199806..... 35
2199807..... 35
2199808..... 35
2199809..... 35
2199810..... 35
2199811..... 35
2199812..... 35
2199814..... 35
2199815..... 35
2199816..... 35
2199817..... 35
2199818..... 35
2199819..... 35
2199829..... 35
3100403....21, 23, 34
3100404..... 21, 23
3100405..... 21, 23
3100412..... 21, 23
3100413..... 21, 23
3100414..... 21, 23
3100425....22, 23, 35
3100426..... 22, 23
3100427..... 22, 23
3100431..... 23
3100432..... 22, 23
3100433..... 23
3590015..... 23
3590016.....23
3590018..... 23
3590019..... 22, 23
3590020..... 23
3590497..... 37
3590498..... 37
3590500 .....20, 23
3590500 ..... 34, 35
3590501..... 23
3590504..... 23
3590509..... 23
3590510..... 23
3590511..... 23
3590514..... 23
3590517..... 23
3590518..... 23
3590540..... 23
3590550..... 23, 37
3590551..... 23
3590560..... 23
3590561..... 23
3590590..... 23
3590591..... 23
3590600..... 23
3590601..... 23
3590630..... 23
3590631..... 23
3590640..... 23
3590641..... 23
3590670..... 23
3590671..... 23
3590680..... 23
3590681..... 23
3591000..... 37
3591001..... 37
3591006..... 37
3591007..... 37
5000003..... 27
8008005..... 37
8308005..... 37
8308006..... 37
AA805AG 23
AA805AG1 23
AA805AG2 23
AB17550 ..... 34, 35
AC202D 27
AC210A1 27
AC210A2 27
AC215A 27
AC215A1 27
AC215A2 27
AC225A1 27
AC230A1 27
AC350A 26
AC351A 26
AJ301A 30
AJ302A 30
AJ303A 30
AJ408AG 30, 34, 35
AJ450A 30
AJ450A6 30
AJ47406 30
AJ47410 ....30, 34, 35
AJ47410A3 30
AJ703A 30
AJ704A 30
AJ720A 31, 34, 35
AJ730A 31, 34, 35
AK020A..... 37
AK020A1..... 37
AK048A..... 7
AK066A..... 7
AK067A..... 37
AK105A..... 37
AK203AG 37
AK203AS..... 37
AK205AG 37
AK205AS..... 37
AK205AT 37
AK206AG 37
AK206AS..... 37
AK207AG 37
AK207AS..... 37
AK210AG 37
AK210AS..... 37
AN111A 30
AN112A 30
AN220A 31

NOTES

capital
SAFETY

INNOVATION THAT BRINGS WORKERS AT HEIGHT HOME SAFELY.

Capital Safety™ is a global company solely dedicated to fall protection and rescue. Our focus is clear. It continually drives us to design and manufacture safe gear that workers want to wear.

Innovation means understanding the industries we serve. We listen to the workers in the field, employ the most engineers, customize solutions, register more new patents and introduce more products. To date, Capital Safety has the best quality and largest breadth of products in the industry. But we're more than a product company.y.

We take an innovative approach in bringing our products to the field. We have created international partnerships and a vast network of certified installers and service centers. We offer on-site and in-house training. And we're ISO 9001-20008 certified for customer service, as well as manufacturing and engineering.

Capital Safety is one of the world's leading manufacturers in fall protection and rescue equipment, with decades of experience and a legacy of innovation. Look for complete solutions in our extensive line of DBI-SALA® and Protecta® products.

PROTECTA®

Capital Safety - USA: 800 328 6146
www.capitalsafety.com **info@capitalsafety.com**

©2015, Capital Safety Form: 9700506 Rev: D