



# Poly-Torq™

## PU (Polyurethane) Gloves

### GL401 Series CE

- 13 gauge nylon liner Grips well without being sticky

---

- Tear and abrasion resistant Offers tactile sensitivity and dexterity

---

- Low particulate shed

Part No.	Sizes
EGL401 •	S, M, L, XL, 2XL

#### Sizing

The color of the binding around the cuff indicates the glove size.

	Small (7) <i>Red</i>		Medium (8) <i>Yellow</i>		Large (9) <i>Brown</i>		X-Large (10) <i>Black</i>		2X-Large (11) <i>Blue</i>
--	-------------------------	--	-----------------------------	--	---------------------------	--	------------------------------	--	------------------------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

#### Materials

- Coating: polyurethane (PU)
- Liner shell: 13 gauge nylon
- Cuff: nylon & latex elastic

Country of Origin: China  
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

#### Cleaning

- Wash in warm water (30-40°C) (86-104°F)
- Use mild detergent
- Short cycle time (5-10 minutes)
- Low tumble dry (60°C max) (140°F max)

Do not use any chemicals or sharp-edged objects for cleaning the gloves. Cleaning can alter the performance levels of the glove.



Abrasion Rated	Circular Blade Cut Rated	Tear Rated	Puncture Rated
1-4	1-5	1-4	1-4

#### Standards

**CE EN388 standard** features abrasion, cut, tear and puncture ratings. Abrasion ratings are based on the number of cycles required to abrade through the sample glove. Cut ratings are based on the number of cycles required to cut through the sample at a constant speed. Tear ratings are based on the amount of force required to tear the sample. Puncture ratings are based on the amount of force required to pierce the sample with a standard-sized point.

#### Testing Performance

##### EN388: 2003

Abrasion (8,070)	1	2	3	4	
Cut	1	2	3	4	5
Tear	1	2	3	4	
Puncture	1	2	3	4	

There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

Gloves meet European EN388:2003 (•) standards. Gloves are sold by the dozen only.  
For specific options visit our website or contact your sales representative.