

Universe	Professional	
Туре	Verticality	
Category	Lanyards and energy absorbers	
Subcategory	Work positioning lanyards	



GRILLON


The GRILLON adjustable lanyard is used to make work positioning systems, to complement a fall-arrest system. Its length can be very easily and precisely adjusted as necessary for comfortable positioning at the work station. Depending on the configuration, it can be used in single or double mode. GRILLON is available in four lengths (2, 3, 4 and 5 m) and also in black. It is certified to North American, European and Russian standards.



GRILLON lanyards are sold without connectors, so that they can be combined with any type of connector, depending on the user's requirements.



The ends are equipped with a plastic sheath that holds the connector in place and protects the rope from abrasion.



Lanyard length is immediately identified by a color-coded label at the connector end.

Short Description Adjustable lanyard for work positioning

Selling Points

- Easy to use: the fine adjustment system allows length to be precisely adjusted for comfortable positioning at a work station
- Can be used in two ways:
- double mode (on the harness side attachment points) when the user works with weight on their feet. This type of attachment gives better load distribution on the belt. Length is adjusted by pressing on the pivoting cam
- single mode, on the harness ventral attachment point, when the anchor is located above the user, so that the load is comfortably distributed between the belt and leg loops. Length is adjusted by operating the handle, while holding the free end of the lanyard
- Sewn terminations on both ends with plastic sheath to keep the connector in position and protect the rope from abrasion
- Protective sheath protects the rope from abrasive contact and enhances rope glide. This protection can be removed for single mode use, to bring the user closer to the anchor
- Available in four lengths: 2, 3, 4 and 5 m. Lanyard length is immediately identified by a color-coded label at the connector end
- Replacement ropes available

Specification

- Material(s): nylon, polyester, aluminum
- Certification(s): ANSI Z359.3, CSA Z259.11, CE EN 358, CE EN 12841 type C, EAC

Specifications by reference

Reference(s)	L052AA00	L052AA01	L052AA02	L052AA03
Length	2 m	3 m	4 m	5 m
Color(s)	white/yellow	white/yellow	white/yellow	white/yellow
Weight	480 g	560 g	640 g	720 g
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Packing	1	1	1	1
Case quantity	10	9	6	6
EAN	3342540821491	3342540821507	3342540821514	3342540821521

Reference(s)	L052AA07	L052AA08
Length	2 m	3 m
Color(s)	black	black
Weight	480 g	560 g
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	1
Case quantity	10	9
EAN	3342540823334	3342540821569

Spare part(s)

Replacement rope for GRILLON
Tubulaire de protection pour GRILLON

Related product(s) Am'D CAPTIV