



All Outlaw series SRL's are part of FrenchCreek's QuickShip service, which means they are eligible for same or next day shipping. Please call for more information.

OUTLAW SRL MODEL SELECTIONS			
Model #	Housing/Swivel Connector*	Lifeline Constituents	Approximate Weight
XR-7W	#354-4 (1" opening steel carabiner)	High Strength Synthetic Webbing	3.5lbs
XR-11G	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	6lbs
XR-11S	#354-4 (1" opening steel carabiner)	Stainless Steel Cable	6lbs
XR-11T	#354-4 (1" opening steel carabiner)	Technora Rope	6lbs
XR-30G	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	10lbs
XR-30S	#354-4 (1" opening steel carabiner)	Stainless Steel Cable	10lbs
XR-30T	#354-4 (1" opening steel carabiner)	Technora Rope	10lbs

*Other housing or swivel connectors may be able upon request

OUTLAW SRL LE MODEL SELECTIONS			
Model #	Housing/Swivel Connector*	Lifeline Constituents	Approximate Weight
XR-20LEG	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	10lbs
XR-30LEG	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	13lbs
XR-50LEG	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	18lbs



All Outlaw series SRL's include: *

#49

Steel swivel locking snaphook, 3/4" gate
Proof loaded up to 3,600 lbs.
Minimum braking load: 5,000 lbs.

***XR-7W includes:**

#Z74

Steel locking snaphook, 3/4" gate
Proof loaded up to 3,600 lbs.
Minimum braking load: 5,000 lbs.



FrenchCreek

FALL SAFETY

frenchcreekproduction.com

©2019 FrenchCreek Production Inc.
100 N. 13th St.
Franklin, PA 16323

Please call to locate your nearest distributor
877.228.9327
814.437.1808

Product descriptions and specifications herein may change without notice.

Outlaw-RevA



THE OUTLAW

SERIES



FrenchCreek

FALL SAFETY

THE OUTLAW SERIES - SELF RETRACTING LIFELINES



Swivel Anchor
Swivels 360° to limit line twisting for smooth operation

Light, Durable Housing
High-strength, light weight housing provides excellent durability

Internal Energy Absorption System
Reduces fall arrest forces and minimizes free fall distance should a fall occur.

Weight Capacity
Outlaw series meets:
ANSI requirement 130-310lbs

OSHA requirement 420lbs or less

Impact Indicator
Locking snap with impact indicator allows for visual inspection of the slightest fall into the unit

Short Fall Arrest Activation
Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 1,800 lb. or less

Lifeline Constituents
Choose the lifeline type to meet the specific needs of your job requirement:
Galvanized Steel
Stainless Steel
Technora® synthetic rope

Meets or Exceed Industry Standards
OSHA Subpart M 1926.502
ANSI A10.32-2012,Z359.14-2014



XR-7W
7' web SRL only
#354-4 (1" opening) steel carabiner
#Z74 (3/4" opening) locking snap
Class "A" SRL



XR-11G
11' galvanized steel cable SRL
#354-4 (1" opening) steel carabiner
#49 (3/4" opening) locking snap
Class "A" SRL

XR-11SS
11' stainless steel cable SRL

XR-11T
11' Technora® synthetic rope SRL



XR-30G
30' galvanized steel cable SRL
#354-4 (1" opening) steel carabiner
#49 (3/4" opening) locking snap
Class "B" SRL

XR-30SS
30' stainless steel cable SRL

XR-30T
30' Technora® synthetic rope SRL



XR-20LEG
Leading Edge SRL
20' galvanized cable only
#354-4 (1" opening) steel carabiner
#49 (3/4" opening) locking snap
Class "B" SRL



XR-30LEG
Leading Edge SRL
30' galvanized cable only
#354-4 (1" opening) steel carabiner
#49 (3/4" opening) locking snap
Class "B" SRL



XR-50LEG
Leading Edge SRL
50' galvanized cable only
#354-4 (1" opening) steel carabiner
#49 (3/4" opening) locking snap
Class "B" SRL

Internal Energy Absorption System
Reduces fall arrest forces and minimizes free fall distance should a fall occur.

Weight Capacity
Outlaw series meets:
ANSI requirement 130-310lbs

OSHA requirement 420lbs or less

Impact Indicator
Locking snap with impact indicator allows for visual inspection of the slightest fall into the unit.



Swivel Anchor Loop
Swivels 360° to limit line twisting for smooth operation.

Light, Durable Housing
High-strength, light weight housing provides excellent durability.

Short Fall Arrest Activation
Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 1,800 lb. or less.

Leading Edge Shock Absorber
Shock pack reduces fall arrest forces. Shock pack free-fall limit 6'. Max elongation distance 48".

Meets or Exceed Industry Standards
OSHA Subpart M 1926.502
ANSI A10.32-2012,Z359.14-2014

Non-Leading Edge

Leading Edge