



V3T™ ANSI CSA BALLISTIC



Vented lens and frame

Quick release strap

Flame resistant foam padding

Passes Ballistic MIL-PRF-32432 High Velocity
Impact standards



Part No.	Black Frame
SB10310ST ●●●	AF Clear
SB10320ST ●●●	AF Gray
SB10330ST ●●●	AF Amber
SB10380ST ●●●	AF I/O Mirror

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet Canadian (CSA Z94.3) (●), or Ballistic (MIL-PRF-32432) (●) standards.

V3T™

General Specifications

Weight: 51.72 gm
PD: 64 mm
Bridge: 24 mm
Lens base: 9 curve
Lens size diagonal: 142 mm
Lens size vertical: 55 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 166 mm
Overall width (hinge - hinge): 142.5 mm
Closest point between temple tips: 65 mm

Materials

Lens: polycarbonate
Frame: nylon
Foam: chloroprene rubber (CR) above and ethylene-vinyl acetate (EVA) sponge
Temple: polycarbonate
Temple tips: thermoplastic rubbers (TPR)
Temple strap holder: nylon
Strap: polyester
Goggle strap holder: polycarbonate
Ratchet: polycarbonate
Nosepiece: chloroprene rubber (CR) foam

Part No.	Lens Marking	Frame Marking
SB10310ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10320ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10330ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10380ST	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
UV Filter Transmittance
U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
L1.7: 55% max visible light
L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967